

## High Power LED VD7000M – for all high-speed camera applications



Standard: Metal-housing

### Highlights

High light intensity max. 7.000lm  
Beam angle 15° oder 28°  
Continuous light (24/7)  
Color spectrum close to daylight  
Flicker-free  
Long-lasting, up to 25´ operating hours  
2 operating modes (normal / boost)  
Ultra-compact robust design  
Active cooling  
Temperature monitoring  
Tripod mount with ¼ inch thread  
Side threads for bracket mounting (4xM5)  
EMC tested /CE conformity



### Technical Data

Lumen (max.)	7.000lm
Metal-housing	57 x 57 x 100 mm
Weight	400g
Beam angle	15° oder 28°
Color temperature	6000K
CRI	≥90
Rated power	72W
Operating voltage	30VDC ±5%
Ambient temperature	-5°C ... +35°C
Boost	≥ 30min



### VD7000M - LED light set

1. 2 x VD7000M Metal-housing
  2. 1 x Switch box
  3. 1 x Power supply 160W
  4. 2 x Connection cable
  5. 1 x Mains cord
  6. 2 x Magic-Arm MA244 with clamp
  7. 2 x Quick-change adapter
  8. 1 x Suitcase iM2600  
(53,8 x 40,6 x 21,1 cm)
  9. Instruction manual
- Order number: 1300040**